

PH 80 PORTABLE LAMP

, , Designed by Poul Henningsen

Type:

Product:

Project:

Modified:



Technical specifications

Materials

Shades: Injection molded PC.

Top, cone, heat sink, stem top, base: Die-casted aluminum.

Stem: Extruded aluminum.

Diffuser: Injection molded clear PC.

Information

Please note that the PH 80 Portable Lamp comes with a USB-cable but without an adapter. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Finishes

White opal shades.

High Lustre Chrome Plated stand with black base or white stand with white base.

Mounting

Cord: 1.5 m. USB-C/USB-C.

Light control: Switch on base.

White light indicator on base when charging.

Batteries: 2 x LiPo, rechargeable, replaceable.

Battery lifetime: 5 hours at 100%.

Dim-2-Warm (1800-2700K) Stepless-dim and 4 step-dim (5%, 20%, 45%, 100%) customer user setting (can switch between the functions). For mounting instructions, see download section

PH 80 PORTABLE LAMP

, , Designed by Poul Henningsen

on the product detail page.

Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5744172325	Integrated LED 1800K-2700K dim-2-warm	5V, 2A/10W	174	-	Without cord	Opal white/high lustre chrome plated	9.1 / 12 / 9.1 in / 1.8 lb
5744172338	Integrated LED 1800K-2700K dim-2-warm	5V, 2A/10W	174	-	Without cord	Opal white/white	9.1 / 12 / 9.1 in / 1.8 lb